



## MULTIMAX MP 515

### Description

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).



### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	445/65R22.5MPT
LI/SS	160;G

## Dimensions US Standard

USA Code	94057207
SW (US) (in)	17.5
OD (US) (in)	45.3
SLR (US) (in)	20.7
RC (US) (in)	139.1
Rim Rec	13
Rim Alt	14
ECE	E11-54R-0017868

## Load Capacity (US)

mph / psi	23	29	36	44	51	58	65	87
55	3840	4540	5310	6060	6780	7470	8380	9920
40	4170	4930	5760	6580	7360	8100	8820	10770
25	4420	5210	6110	6980	7800	8600	9350	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..