



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF710/75R38
LI/SS	183;D

## Dimensions IS Standard

SW (IS) (mm)	720
OD (IS) (mm)	2060
SLR (IS) (mm)	905
RC (IS) (mm)	6151
Rim Rec	DW 24 B
Rim Alt	DW 23 B; DW 25 B
ECE	E11-106R-006764
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3980	4615	5255	5965	6605	7240	7960
from 65 to 40	4375	5075	5775	6560	7260	7960	8750
30	4460	5175	5890	6690	7405	8115	8925
20	4550	5275	6005	6820	7550	8275	9100
10	4810	5580	6350	7215	7985	8755	9625
*Upto 10 Cyc with front loader	6125	7105	8085	9180	10160	11140	12250
10 HT	4460	5175	5890	6690	7405	8115	8925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..