



## SIERRA MAX PRO



### Description

SIERRA MAX PRO is perfect for all-terrain vehicles in ATV applications, also including side-by-side racing. Its radial construction and special wider foot print area provide a smoother ride and an optimized lateral as well as forward traction. Special sturdy lugs have been studied specifically to provide excellent traction and firm grip on the terrain. SIERRA MAX PRO provides excellent performance on every kind of terrain, from hard pack terrains to loose soils.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ ATV

Version

STANDARD

Tyre size

AT27x11R14

LI/SS

56;N

## Dimensions IS Standard

SW (IS) (mm)	285
OD (IS) (mm)	708
SLR (IS) (mm)	336
RC (IS) (mm)	2145
Rim Rec	9.00
ECE	E11-75R-005098

## Load Capacity (IS)

km/h / bar	1.2
140	224

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..