



## FARM 2000

### Description

The FARM 2000 tire is suitable on tractors for soil tillage and transport applications. It is the ideal tire for heavy-duty use and in all operating conditions where good traction is required.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TT
Tyre size	8-18
LI/SS	81;A8

## Dimensions US Standard

USA Code	94045068
SW (US) (in)	7.7
OD (US) (in)	33.1
SLR (US) (in)	15.4
RC (US) (in)	96.8
Rim Rec	W 6
ECE	E11-106R-004084
TRA Code	R1

## Load Capacity (US)

mph / psi	18
25	1020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..