



US standard



GROWING TOGETHER

XL GRIP (T)



PRODUCT DATA SHEET



Bias



XL GRIP (T)

XL GRIP (E-3) best suits on/off trucks carrying heavy loads in mining applications. Its tread compound is designed to minimize cuts and punctures on harshest ground conditions. XL GRIP (E-3) offers exceptional traction and provides an extended tire life-cycle.

Performance



	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM		
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.	
Ø 16"	94060832	8.25 - 16	TT	16	-	STD	-	-	34.3	9.4	-	-	25	63	6.50 H	6.00 G	
	Ø 20"	94015665	10.00 - 20	TT	18	-	STD	-	-	42.3	11.2	19.9	128.2	28	139	7.5	7.0
		94029358	11.00 - 20	TT	18	-	STD	-	-	43.9	11.7	20.8	132.6	31	159	8.0	7.5
		94047789	12.00 - 20	TT	18	-	STD	-	-	45.5	12.6	21.5	136.4	30	183	8.5	8.0
		94047840	12.00 - 20	TT	20	-	STD	-	-	45.5	12.6	21.5	136.4	30	183	8.5	8.0
94061914	12.00 - 20	TT	24	-	STD	-	-	45.5	12.6	21.5	136.4	30	181	8.5	8.0		
Ø 24"	94027590	12.00 - 24	TL	20	-	STD	-	-	49.2	12.6	23.0	146.1	30	216	8.5	8.0	
	94015672	12.00 - 24	TT	20	-	STD	-	-	49.2	12.6	23.0	146.1	30	209	8.5	8.0	
	94031122	12.00 - 24	TT	24	-	STD	-	-	49.2	12.6	23.0	146.1	30	219	8.5	8.0	

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference