



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF900/60R42
LI/SS	195;D

Dimensions IS Standard

SW (IS) (mm)	900
OD (IS) (mm)	2142
SLR (IS) (mm)	944
RC (IS) (mm)	6410
Rim Rec	DW 30B
ECE	E11-106R-0010587

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8
70	4645	5420	6085	6855	7630	8405	9400	10065	11055
from 65 to 40	5105	5955	6685	7535	8385	9235	10330	11060	12150
30	5205	6075	6815	7685	8550	9420	10535	11275	12390
20	5310	6195	6950	7835	8720	9605	10740	11500	12635
10	5615	6550	7355	8290	9225	10160	11365	12165	13365
*Upto 10 Cyc with front loader	7145	8335	9360	10550	11740	12930	14460	15480	17010
10HT	5205	6075	6815	7685	8550	9420	10535	11275	12390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..