



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 48



PRODUCT DATA SHEET



Radial

E-4

B

223

Technologies



All Steel

Performance



Stability



Durability



Traction



Hard Rocky Surface

# EARTHMAX SR 48

RADIAL OTR TIRES



EARTHMAX SR 48 is an All Steel radial tire specially conceived and engineered for rigid haul trucks. It ensures enhanced traction and extraordinary tread resistance even for the most demanding operations in rocky environments. This tire is ideal for handling heavy loads. The square shoulder design protects the sidewall against cuts and damage. EARTHMAX SR 48 has a strong All Steel casing which provides exceptional protection against shocks and rock perforation resulting in enhanced productivity.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 35"	24.00 R 35	TL	E-4	**	209 B	CRC	310	665	2180	993	6621	58	17.00/3.5	-
	24.00 R 35	TL	E-4	**	209 B	STDC	377	665	2180	993	6621	58	17.00/3.5	-
Ø 49"	27.00 R 49	TL	E-4	**	223 B	CRC	440	738	2688	1225	8165	68	19.50/4.0	-
	27.00 R 49	TL	E-4	**	223 B	HRC	600	738	2688	1225	8165	68	19.50/4.0	-
	27.00 R 49	TL	E-4	**	223 B	STDC	510	738	2688	1225	8165	68	19.50/4.0	-

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference