



## LUG STAR

### Description

LUG STAR is an industrial tire designed for road-rail excavator applications where exceptional traction is required. It features excellent self-cleaning properties and a very resistant tread compound. The robust casing provides excellent durability.

### UM

IS Standard

### Construction

 Bias

### Machinery

Industrial & Construction ■ Road Rail Equipment



|           |          |
|-----------|----------|
| Version   | STANDARD |
| Tire Type | TT       |
| Tyre size | 10.00-20 |
| LI/SS     |          |

## Dimensions IS Standard

|               |          |
|---------------|----------|
| OD (IS) (mm)  | 1080     |
| SLR (IS) (mm) | 506      |
| RC (IS) (mm)  | 3343     |
| Rim Rec       | 7.5      |
| Rim Alt       | 7.0; 8.0 |

## Load Capacity (IS)

|            |       |
|------------|-------|
| km/h / bar | 10.00 |
| 10         | 6890  |
| 25         | 5300  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..