



LG RIB

Description

LG RIB is a lawn and garden tire suitable for mowers and small tractors. Its tread pattern has been designed for making the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG RIB is available in an "aramid-belted" version for users who need strengthened puncture resistance.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Mower



Version

ARAMID BELTED

Tire Type

TL

Tyre size

15x6.00-6

LI/SS

Dimensions IS Standard

SW (IS) (mm)	152
OD (IS) (mm)	365
SLR (IS) (mm)	159
RC (IS) (mm)	1059
Rim Rec	4.50 A
ECE	E11-106R-003504

Load Capacity (IS)

km/h / bar	3.20
15	335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..