



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 513



PRODUCT DATA SHEET



Radial



155



MULTIMAX MP 513

RADIAL MPT TIRES

🇬🇧 MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

Technologies



High Speed



Steel Belted

Performance



Handling and Comfort



Self-Cleaning



Traction



Durability

	Tire size	Type	STAR RATING	LI/SS	Version	S.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 16"	285/80 R 16 MPT	TL	-	128 G	STD	304	866	394	2617	W 10	-
Ø 17"	425/55 R 17 MPT	TL	-	142 A8/B	STD	421	900	399	2705	13	13.00
	425/55 R 17 MPT	TL	-	134 G	STD	421	900	399	2695	13	13.00
Ø 18"	325/70 R 18 MPT	TL	-	132 G	STD	322	916	410	2771	W 10	-
	365/70 R 18 MPT	TL	-	133 G	STD	360	969	448	2954	11	11 SDC; 12; 12 SDC
Ø 20"	375/70 R 20 MPT	TL	-	136 G	STD	377	1034	472	3121	12	W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC
	405/70 R 20 MPT	TL	-	136 G	STD	407	1076	493	3253	13	13 SDC; 12 SDC
	425/75 R 20 MPT	TL	-	148 G	STD	421	1146	518	3465	13	13 SDC; 11 SDC; 12 SDC; 11; 12
Ø 24"	495/70 R 24 MPT	TL	-	155 G	STD	499	1304	588	3974	W 16 L	DW 15 L; DW 16 L; W 15 L

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference