



MP 590

Description

MP 590 is an agro-industrial tire suitable for loading operations with telehandlers and forklifts. This tire provides good traction and excellent stability as well as increased durability.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ▪ Telehandler, Industrial & Construction ▪ Forklift



Version	STANDARD
Tire Type	TL
Tyre size	18-22.5
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	480
OD (IS) (mm)	1190
SLR (IS) (mm)	530
RC (IS) (mm)	3534
Rim Rec	14.0
ECE	E11-106R-004408

Load Capacity (IS)

km/h / bar	7.50
40 DW	5800
30 DW	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..