



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 423



PRODUCT DATA SHEET



Radial



EARTHMAX SR 423

RADIAL OTR TIRES

EARTHMAX SR 423 is an All Steel radial tire suitable for a variety of applications including quarry, haulage and logging operations. The non-directional tread pattern provides excellent traction and stability on any type of terrain. The tire is ideal for handling heavy loads. The strong *All Steel* casing features excellent wear and resistance to snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under heavy-duty service conditions.

Technologies



All Steel

Performance



Durability



High Load Capacity



Comfort

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 20"	10.00 R 20	TT	-	-	149/146 J	STD	-	270	1065	-	-	20	7.50	8.00
	11.00 R 20	TT	-	-	152/149 J	STD	-	285	1100	-	-	20	8.00	8.50
	12.00 R 20	TT	-	-	154/150 J	STD	-	302	1132	-	-	22	8.50	9.00
Ø 24"	12.00 R 24 (325/95 R 24)	TT	-	-	160/156 K	STD	-	318	1243	-	-	22	8.50	-
	325/95 R 24 (12.00 R 24)	TT	-	-	160/156 K	STD	-	318	1243	-	-	22	8.50	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference