



US standard



GROWING TOGETHER

# FORESTMAX



PRODUCT DATA SHEET

# FORESTMAX



FORESTMAX is BKT's new radial tire for tractors, which has been mainly developed for forestry applications, but can also be employed for some specific farming operations such as soil milling and stone breaking. Its multi-ply polyester casing and the reinforced sidewall are designed to withstand the harsh forestry operating conditions. In addition, the cut-and-chip-resistant tread compound and the steel-belted structure significantly minimize the risk of punctures in the woodland. The tire features a robust open shoulder providing best traction and top stability even on rugged and uneven terrains. The combination of tread resistance and the particular shoulder design stand for optimum self-cleaning properties along with a long tire life making FORESTMAX your ideal partner in the forest.



Radial



**Technologies**



Strong Casing



Steel Belted



Special Compound

**Performance**



Cut and Chip Resistance



Traction



Stability



Self-Cleaning



High Puncture Resistance



Durability

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 28"	94074679	540/65 R 28	149 A8/ 146 B	W 18 L	-	21.7	55.6	25.6	167.2	63	327	SB
	94512850	<b>600/60 R 28</b> NEWSIZE	152 A8/ 149 B	DW 18 L	DW 20 B	22.4	56.3	25.8	169.9	64	370	SB
Ø 38"	94074044	650/65 R 38	164 A8/ 160 B	DW 20 B	DW 21 B ; DW 23 B	25.4	71.3	32.8	215.2	64	592	SB
	94076437	<b>650/65 R 38</b> NEWSIZE	172 A8/ 186 A2	DW 20 B	DW 21 B ; DW 23 B	25.4	71.3	32.8	215.2	64	598	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference