



AGRIMAX RT 765



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

IS Standard

Construction

Machinery

Agriculture ▪ Sprayer

Version	SPECIAL
Tire Type	TL
Tyre size	620/70R42
LI/SS	173;D

Dimensions IS Standard

SW (IS) (mm)	625
OD (IS) (mm)	1935
SLR (IS) (mm)	876
RC (IS) (mm)	5804
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-005833
TRA Code	R1W

field_1

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2		
65	2535	2990	3445	3835	4290	4680	5135	5525	6045	6500		
50	2665	3140	3620	4030	4505	4915	5395	5805	6350	6825		
40	2780	3280	3775	4205	4700	5130	5625	6055	6625	7120		
30	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475		
10 LT	3400	4010	4620	5140	5750	6275	6885	7405	8105	8710		
10 HT	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..