



US standard



GROWING TOGETHER

FLOTATION 351



PRODUCT DATA SHEET



Bias



Performance



High Load Capacity



Durability



Traction



FLOTATION 351

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 20"	94006595	42 X 25.00 - 20	20.50 HF	20.50 VF	23.8	43.7	20.0	130.0	47	241	STD	12	TL	135 B
	94033652	42 X 25.00 - 20	20.50 HF	20.50 VF	23.8	43.7	20.0	130.0	47	262	STD	16	TL	139 B
	94025657	48 X 25.00 - 20	20.50 HF	20.50 VF	24.8	50.0	22.0	149.0	59	315	STD	10	TL	144 B
	94026135	48 X 31.00 - 20	26.00 HF	26.00 VF	30.5	50.5	22.0	153.0	59	394	STD	12	TL	148 B
Ø 25"	94042999	66 X 43.00 - 25	36.0 TH	-	40.2	68.9	30.8	205.2	75	692	STD	6	TL	150 B
	94029327	66 X 43.00 - 25	36.0 TH	-	40.2	68.9	30.8	205.2	75	834	STD	10	TL	160 B
	94029495	66 X 43.00 - 25	36.0 TH	-	40.2	68.9	30.8	205.2	75	885	STD	16	TL	170 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference