



AS 504

Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Telehandler, Industrial & Construction ■
Telehandler



Version

STANDARD

Tire Type

TT

Tyre size

5.00-15

LI/SS

Dimensions IS Standard

SW (IS) (mm)	140
OD (IS) (mm)	657
SLR (IS) (mm)	308
RC (IS) (mm)	1957
Rim Rec	3.50 D
Rim Alt	3.00 D; 4.00 E; 4 J
ECE	E11-106R-004237

Load Capacity (IS)

km/h / bar	02:30:00																		
10 FR	610																		
25 FR	520																		
30 FR	485																		
40 FR	435																		
10 DW	425																		
25 DW	365																		
30 DW	340																		
40 DW	305																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..