



## EARTHMAX SR 32



### Description

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Scraper

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 37.25R35

LI/SS 218;B

## Dimensions IS Standard

OD (IS) (mm)	2381
SLR (IS) (mm)	1062
RC (IS) (mm)	7229
Rim Rec	31.00/4.0
TRA Code	E3

## Load Capacity (IS)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	19500	20600	21200	22400	23000	23600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..