



AS 504

Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Implement Machinery, Industrial & Construction ■ Telehandler



Version	STANDARD
Tire Type	TT
Tyre size	7.50-16
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	209
OD (IS) (mm)	803
SLR (IS) (mm)	372
RC (IS) (mm)	2475
Rim Rec	5.50 F
Rim Alt	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
ECE	E4-106R-002633

Load Capacity (IS)

km/h / bar	03:20:00																		
10 FR	1570																		
25 FR	1335																		
30 FR	1255																		
40 FR	1120																		
10 DW	1085																		
25 DW	920																		
30 DW	870																		
40 DW	775																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..