



FL 633 PERFORMA

Description

The new All Steel radial tire FL 633 PERFORMA perfectly combines the needs of several agricultural applications with the growing demand for logistics in agriculture. Specifically designed for agro trucks, FL 633 PERFORMA is the innovative solution that enhances both tractor and truck performance features. Thanks to its very strong casing, FL 633 PERFORMA is suitable for multiple activities in the fields and even for travel on highways reaching up to 100 km/h.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Agro Truck

Version	STANDARD
Tire Type	TL
Tyre size	600/50R22.5
LI/SS	164;J

Dimensions IS Standard

OD (IS) (mm)	1170
SLR (IS) (mm)	534
RC (IS) (mm)	3559
Rim Rec	AG 20.00
ECE	E11-54R-0017858

Load Capacity (IS)

km/h / bar	06:50:00
100	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1-04-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..