



## AGRIMAX RT 765



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	420/70R30
LI/SS	134;D

## Dimensions US Standard

USA Code	94063062
SW (US) (in)	16.5
OD (US) (in)	55.0
SLR (US) (in)	24.8
RC (US) (in)	164.3
Rim Rec	W 13
Rim Alt	W 12; W 14 L
ECE	E11-106R-005830
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23
40	2580	3000	3420	3840	4250	4670
30	2710	3150	3590	4030	4480	4920
25	2820	3280	3750	4210	4670	5130
20	2970	3450	3940	4420	4910	5380
5 LT	3450	4020	4590	5150	5710	6270
5 HT	2970	3450	3940	4420	4910	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..