



US standard



GROWING TOGETHER

# AGRIMAX

RADIAL TRACTOR TIRES

## TERIS



PRODUCT DATA SHEET



Radial



185



# AGRIMAX TERIS

RADIAL TRACTOR TIRES

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance – thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

### Technologies



Reinforced Shoulder



Special Compound



Reinforced Bead

### Performance



Traction



High Load Capacity



High Puncture Resistance



Stability



Handling and Comfort

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 26"	94035809	620/75 R 26 CHO	166 A8/B	DW 20 B	-	24.6	62.6	28.7	191.0	62	452	STD
	94030668	750/65 R 26 CHO (28 L R 26)	166 A8/B	DW 25 B	DW 23 B	30.1	64.4	28.1	193.2	61	533	STD
	94039111	750/65 R 26 CHO (28 L R 26)	171 A8/B	DW 25 B	DW 23 B	30.1	64.4	28.1	193.2	61	539	STD
Ø 28"	94060023	710/55 R 28 CHO	164 A8/B	DW 23 B	-	28.2	58.8	26.1	174.9	67	420	STD
Ø 30"	94039586	620/75 R 30 CHO	168 A8/B	DW 20 B	-	24.6	66.6	30.7	203.5	62	487	STD
Ø 32"	94032860	650/75 R 32 CHO	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	26.4	70.7	32.1	211.7	75	580	STD
	94059249	IF 710/75 R 32 CFO	183 A8/B	DW 25 B	DW 23 B	28.2	74.0	33.5	222.6	77	744	STD
	94031412	800/65 R 32 CHO (30.5 L R 32)	178 A8/ 175 B	DW 27 B	DW 25 B ; DH 27 B	32.2	73.0	33.0	218.5	71	730	STD
	94029723	900/60 R 32 CHO	181 A8/ 178 B	DW 27 B	DW 28 B ; DW 30 B	34.9	75.2	33.6	224.4	74	878	STD
	94040865	900/60 R 32 CHO	185 A8/ 182 B	DW 27 B	DW 28 B ; DW 30 B	34.4	75.2	34.4	227.4	74	895	STD
	94032723	1050/50 R 32 CHO	184 A8/ 181 B	36.0 VA (multipiece)	-	41.7	74.5	33.1	223.8	75	1020	STD
	94076185	1050/50 R 32 CHO	184 A8/ 181 B	36.0 VA (multipiece)	-	41.7	74.5	33.1	223.8	75	1055	HD

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Reinforced Shoulder



Special Compound



Reinforced Bead

Performance



Traction



High Load Capacity



High Puncture Resistance



Stability



Handling and Comfort

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 34"	94044641	IF 580/80 R 34 CFO	177 D	DW 20 B ; DW 20 A	DW 21 A ; DW 21 B	23.1	70.6	31.9	213.5	71	520	STD
	94058723	IF 710/75 R 34 CFO	184 A8/B	DW 25 B	-	28.2	76.0	34.3	230.4	77	775	STD
Ø 42"	94044634	520/85 R 42	168 D	DW 16 L	W 15 L ; DW 15 L ; DD 16 L ; W 16 L ; DD 18 L ; DW 18 L ; W 18 L	20.3	76.8	35.0	230.4	71	518	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference