



EM 937 IND3 (ECH)



Description

EM 937 (E-3) IND is specially designed for empty-container-handling operations in stacking and loading applications. It features excellent durability and a long tire life. EM 937 (E-3) IND is ideal on paved surfaces and for all operations requiring a high level of handling in the port.

UM

US Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Empty Container Handler

Version	PORT INDUSTRIAL
Tire Type	TL
Tyre size	14.00-24
LI/SS	

Dimensions US Standard

USA Code	94043996
OD (US) (in)	53.9
SLR (US) (in)	24.7
RC (US) (in)	159.4
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND3

Load Capacity (US)

mph / psi	145
5	29750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..