



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 459



PRODUCT DATA SHEET

EARTHMAX SR 459

RADIAL OTR TIRES



EARTHMAX SR 459 is an All-Steel radial tire for rigid dump trucks operating in quarries and open pit mines. Its specifically developed symmetric design ensures excellent durability on both rear and front axles. The multiple steel belts provide superior protection against shocks and rock penetration, whilst the high tread depth ensures optimal protection to the carcass and a long tire life. In addition, the close tread design maximizes ground contact resulting in excellent stability as well as great operator comfort. EARTHMAX SR 459 stands out for excellent traction on any ground, even on muddy surfaces.



Radial



Technologies



All Steel Radial



Extra Deep Tread



Heavy Duty



Strong Casing



Reinforced Carcass

Performance



Durability



Cut and Chip Resistance



Hard Rocky Surface



Handling and Comfort



Traction

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 49"	94512591	27.00 R 49	TL	**	223 B	CRC	E-4	280	107.1	29.4	48.5	324.6	102	3311	19.50/4.0	-
	94513062	27.00 R 49	TL	**	223 B	STDC	E-4	325	107.1	29.4	48.5	324.6	102	3296	19.50/4.0	-
	94513048	27.00 R 49	TL	**	223 B	HRC	E-4	358	107.1	29.4	48.5	324.6	102	3300	19.50/4.0	-

CRC: Cut Resistance Compound - STDC: Standard Compound - HRC: Heat Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference