



## AGRIMAX PROCROP



### Description

AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version STEEL BELTED

Tire Type TL

Tyre size VF270/95R36

LI/SS 150;D

## Dimensions IS Standard

SW (IS) (mm)	280
OD (IS) (mm)	1441
SLR (IS) (mm)	665
RC (IS) (mm)	4393
Rim Rec	W9
ECE	E11-106R-0010172

## Load Capacity (IS)

km/h / bar	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1435	1620	1800	1955	2170	2290	2505	2715	2900	3050
from 65 to 40	1575	1780	1980	2145	2380	2515	2750	2985	3185	3350
30	1610	1815	2020	2190	2430	2565	2805	3045	3250	3420
20	1640	1850	2060	2235	2475	2615	2860	3105	3315	3485
10	1735	1955	2175	2360	2620	2765	3025	3280	3505	3685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..