



TF 8181

Description

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

UM

IS Standard

Construction

▣ Bias

Machinery

Agriculture ■ 2WD Tractor, Industrial & Construction ■ Trailer



Version	STANDARD
Tire Type	TT
Tyre size	6.50-20
LI/SS	97;A6

Dimensions IS Standard

SW (IS) (mm)	180
OD (IS) (mm)	865
SLR (IS) (mm)	409
RC (IS) (mm)	2578
Rim Rec	5.00 F
Rim Alt	4.00 E; 5.50 F
ECE	E4-106R-001964
TRA Code	F2

Load Capacity (IS)

km/h / bar	03:10:00																		
30	730																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..