



TR 135

Description

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

UM

IS Standard

Construction

⊠ Bias

Machinery

Agriculture ■ Tractor, Industrial & Construction ■ Trailer



Version

STANDARD

Tire Type

TT

Tyre size

9.5-30

LI/SS

115;A6

Dimensions IS Standard

SW (IS) (mm)	241
OD (IS) (mm)	1200
SLR (IS) (mm)	567
RC (IS) (mm)	3528
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-004433
TRA Code	R1

Load Capacity (IS)

km/h / bar	03:20:00																		
30	1215																		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..