



US standard



GROWING TOGETHER

FLOTATION 648 T



PRODUCT DATA SHEET



Bias



166



FLOTATION 648 T

FLOTATION 648 T is particularly suitable for hay harvesting as well as for field and road transport. The special tread design allows for carrying very heavy loads at low pressure and ensures outstanding self-cleaning properties. The tire also stands for excellent traction and durability.

Performance



Durability



High Load Capacity



Traction

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 22.5"	94029242	550/45 - 22.5	AG 16.00	-	21.7	42.1	18.7	126.1	27	179	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B
	94052066	550/45 - 22.5	AG 16.00	-	21.7	42.1	18.7	126.1	27	166	STD	16	TL	147 A8/ 144 B	159 A8/ 156 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling