



TR 459

Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ■ Tractor, Industrial & Construction ■
Backhoe Loader



Version	INDUSTRIAL
Tire Type	TL
Tyre size	19.5L-24
LI/SS	147;A8

Dimensions US Standard

USA Code	94016662
SW (US) (in)	19.3
OD (US) (in)	52.5
SLR (US) (in)	23.0
RC (US) (in)	158.7
Rim Rec	DW 16 L
ECE	E11-106R-005334
TRA Code	R4

Load Capacity (US)

mph / psi	28
25	6800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..