



## AW 909

### Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

### UM

US Standard

### Construction

◆ Bias

### Machinery

Agriculture ■ Baler



Version	STANDARD
Tire Type	TL
Tyre size	10.0/75-15.3
LI/SS	

## Dimensions US Standard

USA Code	94010448
SW (US) (in)	10.8
OD (US) (in)	29.9
SLR (US) (in)	13.5
RC (US) (in)	87.7
Rim Rec	9.00
ECE	E4-106R-001544

## Load Capacity (US)

mph / psi	80
5 FR	5860
15 FR	4980
20 FR	4700
25 FR	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..