



AIROMAX AM 27



Description

AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.

UM

US Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Mobile Crane

Version	STANDARD
Tire Type	TL
Tyre size	505/95R25
LI/SS	186;E

Dimensions US Standard

USA Code	94045198
OD (US) (in)	63.0
SLR (US) (in)	28.7
RC (US) (in)	192.9
Rim Rec	13.00/2.5

Load Capacity (US)

mph / psi	130
20	27200
25	26000
30	24700
35	23500
43	20900
50	17200
55	14700
62	12600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..