



AGRIMAX SPARGO SB



Description

AGRIMAX SPARGO SB is a special row crop tire that is particularly suitable for tractors and sprayers in open-field spraying and row crop applications, or for specialized tractors in orchards and vineyards. Thanks to its advanced VF-technology (Very Increased Flexion), the tire is able to carry 40% heavier load compared to a standard tire of the same size at the same inflation pressure. The wide footprint ensures uniform weight distribution as well as low soil compaction in the fields.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF270/95R38
LI/SS	151;D

Dimensions IS Standard

SW (IS) (mm)	280
OD (IS) (mm)	1491
SLR (IS) (mm)	692
RC (IS) (mm)	4546
Rim Rec	W9
ECE	E11-106R-0010500

Load Capacity (IS)

km/h / bar	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1480	1665	1855	2010	2230	2355	2575	2795	2985	3140
from 65 to 40	1625	1830	2040	2210	2450	2590	2830	3075	3280	3450
30	1655	1870	2080	2255	2500	2640	2890	3135	3345	3520
20	1690	1905	2120	2300	2550	2695	2945	3200	3415	3590
10	1785	2015	2240	2430	2695	2850	3115	3380	3610	3795

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..