



IS standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

TURF RT 333



PRODUCT DATA SHEET



Radial

R-1W

B

149

AGRIMAX TURF RT 333

RADIAL TRACTOR TIRES



AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 12"	220/55 R 12	82 A8/B	7	-	221	550	249	1645	260	STD
	240/60 R 12	89 A8/B	7	-	242	592	269	1777	-	STD
Ø 14"	215/65 R 14	90 A8/ 90 B	W 7	W 6	220	630	290	1906	310	STD
Ø 16"	200/65 R 16	94 A8/B	W 6	-	202	666	309	2000	320	STD
	200/70 R 16	94 A8/B	W 6	-	200	686	317	2054	330	STD
	240/70 R 16	104 A8/B	W 8	W 8 L; W 9	244	742	340	2213	350	STD
	260/70 R 16	109 A8/ 109 B	W 8	W 8 L; W 9	258	770	348	2287	370	STD
Ø 18"	280/70 R 16	112 A8/ 112 B	W 9	W 8; W 10	289	800	359	2371	380	STD
	280/70 R 18	114 A8/ 114 B	W 9	W 8; W 10	289	840	390	2550	400	STD
	320/65 R 18	109 A8/ 109 B	W 10	W 9; W 11	319	873	394	2591	425	STD
Ø 20"	300/70 R 20	110 A8/ 110 B	W 9	W 10	295	952	431	2826	450	STD
	320/70 R 20	113 A8/ 113 B	W 10	W 9; W 11	319	982	441	2916	475	STD
	380/70 R 20	122 A8/ 122 B	W 12	W 11; W 13	380	1082	486	3213	525	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



Technologies



Extra Deep Tread



Block Pattern

Performance



Durability



Reduced Soil Compaction



Traction



Self-Cleaning



Low Rolling Resistance



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	360/70 R 24	122 A8/ 122 B	W 11	W 10 ; W 12	357	1152	518	3409	550	STD
	380/70 R 24	125 A8/ 125 B	W 12	W 11 ; W 13	380	1190	534	3538	550	STD
	420/70 R 24	130 A8/ 130 B	W 13	W 12 ; W 14 L	418	1248	557	3728	600	STD
	420/85 R 24	137 A8/ 137 B	W 15 L	DW 15 L ; DW 14 L	435	1324	594	3957	625	STD
Ø 28"	340/85 R 28	127 A8/ 127 B	W 12	W 11 ; DW 11 ; DW 12	370	1289	585	3874	625	STD
	480/70 R 28	140 A8/ 140 B	W 15 L	W 14 L ; W 16 L	479	1421	631	4228	675	STD
Ø 30"	480/70 R 30	141 A8/ 141 B	W 15 L	W 14 L ; W 16 L	479	1478	660	4396	700	STD
Ø 34"	480/70 R 34	149 A8/ 149 B	W 15 L	W 14 L ; W 16 L	490	1580	723	4785	750	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index