



US standard



GROWING TOGETHER

LIFTMAX LM 81



PRODUCT DATA SHEET



Radial



LIFTMAX LM 81

LIFTMAX LM 81 has been specifically designed and engineered for heavy forklift. Its aggressive and robust tread pattern together with the unique Antistatic tread compound ensures excellent wear properties and a long service life. The strong All Steel casing and the reinforced sidewall provide maximum stability and handling during lift mode, together with superior traction. In addition, its radial casing absorbs surfaces irregularities to provide better riding comfort and increase operator's confidence. LIFTMAX LM 81 is Antistatic compliant, and all its sizes are capable of dissipating static charge from the vehicle.

Technologies



Special Antistatic Compound



All Steel

Performance



Stability



Durability



Handling and Comfort



Traction

	US CODE	Tire size	Type	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
						(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 8"	94059423	5.00 R 8	TL	111 A5	STD	18.5	5.4	-	-	29	23	3.00 D	3.25 I; 3.75 I
	94069316	150/75 R 8	TL	113 A5	STD	16.9	5.9	-	-	20	21	4.33 R	-
	94075423	150/75 R 8 IMP	TL	109 A8	STD	16.9	5.9	-	-	20	21	4.33 R	-
	94063642	180/70 R 8	TL	125 A5	STD	17.8	6.7	-	-	21	25	4.33 R	-
	94067596	180/70 R 8 IMP (18 X 7 R 8)	TL	120 A8	STD	17.8	6.7	-	-	21	25	4.33 R	-
Ø 9"	94048878	6.00 R 9	TL	121 A5	STD	21.3	6.3	-	-	31	35	4.00 E	-
	94069200	200/75 R 9	TL	134 A5	STD	20.9	8.0	-	-	28	38	6.00 E	-
Ø 10"	94048885	6.50 R 10	TL	128 A5	STD	23.2	7.0	-	-	35	47	5.00 F	5.50 F
	94060467	225/75 R 10	TL	142 A5	STD	23.4	8.7	-	-	29	49	6.50 F	-
Ø 12"	94044979	7.00 R 12	TL	136 A5	STD	26.6	7.7	-	-	35	61	5.00 S	-
	94051724	250/75 R 12	TL	152 A5	STD	26.8	10.2	-	-	33	77	8.00	-
Ø 15"	94052820	7.00 R 15	TL	143 A5	STD	29.3	7.8	-	-	35	75	5.50	5.00
	94048847	7.50 R 15	TL	146 A5	STD	30.6	8.3	-	-	37	85	6.00	6.50
	94052950	8.25 R 15	TL	153 A5	STD	32.9	9.2	-	-	42	110	6.50	7.00

STD: Standard

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial



Technologies



Special Antistatic Compound



All Steel

Performance



Stability



Durability



Handling and Comfort



Traction



	US CODE	Tire size	Type	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
						(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 15"	94052967	225/75 R 15 (28 X 9 R 15)	TL	149 A5	STD	28.0	8.9	-	-	30	73	7.00	-
	94062904	250/70 R 15	TL	153 A5	STD	28.9	9.1	-	-	33	80	7.00	7.50
	94067657	315/70 R 15	TL	165 A5	STD	32.8	12.0	-	-	40	129	8.00	-
	94513352	355/65 R 15	TL	170 A5	STD	33.1	13.8	-	-	44	149	10.15	-
Ø 20"	94073177	9.00 R 20	TL	160 A5	STD	40.4	10.0	-	-	42	191	7.00	7.50
	94049004	10.00 R 20	TL	166 A5	STD	42.0	10.8	-	-	44	218	7.50	8.00
	94053728	11.00 R 20	TL	170 A5	STD	43.0	11.3	-	-	47	220	8.00	8.50
	94053025	12.00 R 20	TL	176 A5	STD	44.6	12.4	-	-	49	262	8.50	8.00
	94070534	12.00 R 20	TL	176 A5	IND	44.6	12.4	-	-	49	263	8.50	8.00
Ø 24"	94056989	12.00 R 24	TT	178 A5	STD	48.6	12.2	-	-	49	274	8.50	9.00
	94069668	12.00 R 24	TL	178 A5	STD	48.6	12.2	-	-	49	274	8.50	9.00
	94058549	14.00 R 24	TL	193 A5	STD	55.7	15.3	-	-	78	531	10.00 W	10.0 ; 10.00 WA
	94070541	14.00 R 24	TL	193 A5	IND	55.7	15.3	-	-	78	530	10.00 W	10.0 ; 10.00 WA
Ø 25"	94069071	16.00 R 25	TL	200 A5	STD	60.2	17.3	-	-	88	767	11.25/2.00	13.00/2.00

STD: Standard - IND: Industrial

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference