



EARTHMAX SR 51 SP

Description

EARTHMAX SR 51 SP is an All-Steel radial tire specifically developed for medium-sized wheel loaders operating in severe mining and quarrying environments. The reinforced, strong casing delivers maximum performance during demanding loading, dozing, and load-and-carry operations on mixed surfaces, such as unpaved roads, gravel, and crushed rock. Thanks to its high rubber volume and tread density, the deep L5 tread combines high traction with excellent resistance to damage while the non-directional design ensures uniform driving characteristics and extended wear resistance. Moreover, the cut-resistant compound provides extraordinary protection against punctures.



UM

US Standard

Construction

 Radial

Machinery

OTR ■ Loader

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	35/65R33
LI/SS	229;A2

Dimensions US Standard

USA Code	94069866
OD (in)	81.1
SLR (in)	34.3
RC (in)	239.4
Rim Rec	28.00/3.5
TRA Code	L5

Load Capacity (US)

mph / psi	98	102	105	109	112	116
5	64000	66000	68000	69500	70500	71500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 20-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..