



US standard



GROWING TOGETHER

# AGRIMAX FORTIS

RADIAL EXTRA LARGE TIRES



PRODUCT DATA SHEET



Radial



Technologies



High Speed



Reinforced Carcass

Performance



Traction



High Load Capacity



Handling and Comfort



Reduced Soil Compaction



# AGRIMAX FORTIS

RADIAL EXTRA LARGE TIRES

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 30"	94032952	600/70 R 30	158 D/ 161 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.5	189.4	72	397	STD
	94058914	600/70 R 30	158 D/ 161 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.5	189.4	72	398	SPL
Ø 34"	94035649	600/70 R 34	160 D/ 163 A8	DW 18 L	DW 20 B ; W 18 L	23.3	67.1	30.0	201.1	72	428	STD
	94050116	600/70 R 34	160 D/ 163 A8	DW 18 L	DW 20 B ; W 18 L	23.3	67.1	30.0	201.1	72	429	SPL
Ø 38"	94029730	650/85 R 38	173 D/ 176 A8	DW 23 B	DW 21 B ; DW 20 B	26.6	81.5	36.8	243.5	81	772	STD
	94058907	650/85 R 38	173 D/ 176 A8	DW 23 B	DW 21 B ; DW 20 B	26.6	81.5	36.8	243.5	81	772	SPL
	94032969	800/70 R 38	178 D/ 181 A8	DW 25 B	DW 27 B	31.4	82.1	35.9	244.2	75	854	STD
Ø 42"	94034710	710/75 R 42	175 D/ 172 E	DW 23 B	DW 25 B	28.2	84.0	38.2	252.2	77	853	STD
	94050123	710/75 R 42	175 D/ 172 E	DW 23 B	DW 25 B	28.2	84.0	38.2	252.2	77	855	SPL

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference