



## AGRIMAX V-FLECTO

### Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version	STEEL BELTED SPL
Tire Type	TL
Tyre size	VF900/65R46
LI/SS	193;D

## Dimensions IS Standard

SW (IS) (mm)	900
OD (IS) (mm)	2338
SLR (IS) (mm)	1006
RC (IS) (mm)	7003
Rim Rec	DW 30B
ECE	E11-106R-0010524

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
<b>70</b>	5335	6170	7010	7950	8685	9415	10465
<b>from 65 to 40</b>	5865	6785	7705	8740	9545	10350	11500
<b>30</b>	5980	6920	7855	8910	9735	10555	11730
<b>20</b>	6095	7055	8010	9085	9925	10760	11960
<b>10</b>	6450	7460	8475	9610	10495	11385	12650
<b>Upto 30 Cyc</b>	6655	7695	8740	9915	10830	11745	13050
<b>Upto 15 Cyc</b>	7945	9190	10435	11840	12930	14020	15580
<b>Upto 10 Cyc</b>	8705	10070	11440	12975	14170	15365	17075
<b>10HT</b>	5980	6920	7855	8910	9735	10555	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..