



AGRIMAX PROCROP



Description

AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version STEEL BELTED

Tire Type TL

Tyre size VF230/95R48

LI/SS 148;D

Dimensions US Standard

USA Code	94514441
SW (US) (in)	9.2
OD (US) (in)	65.4
SLR (US) (in)	30.9
RC (US) (in)	200.8
Rim Rec	W8
Rim Alt	W7
ECE	E11-106R-0011158

Load Capacity (US)

mph / psi	14	17	20	23	29	35	41	46	52	58
45	2980	3370	3740	4060	4500	4760	5200	5640	6020	6330
from 40 to 25	3280	3690	4110	4460	4940	5220	5700	6190	6610	6950
20	3340	3760	4190	4550	5040	5330	5820	6320	6740	7090
12	3410	3840	4280	4630	5140	5430	5940	6440	6880	7240
5	3600	4060	4510	4900	5440	5740	6280	6810	7270	7640
Upto 10 Cyc.	4440	5000	5560	6030	6700	7070	7730	8390	8960	9420
Upto 20 Cyc.	3720	4190	4670	5060	5620	5920	6490	7040	7510	7900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..