



INDUSTRIAL RIB F3



Description

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

UM

US Standard

Construction

Machinery

Agriculture ▪ Implement Machinery

Version STUBBLE RESISTANT

Tire Type TL

Tyre size 11L-15SL

LI/SS 114;A6

Dimensions US Standard

USA Code	94055494
SW (US) (in)	11.0
OD (US) (in)	32.0
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-006914
TRA Code	F3

field_2

mph / psi	52
20	2610
25	2340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..