



## AGRIMAX RT 657



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Vineyard Harvester

Version STANDARD

Tire Type TL

Tyre size 650/65R38

LI/SS 163;D

## Dimensions US Standard

USA Code	94021383
SW (US) (in)	25.4
OD (US) (in)	71.3
SLR (US) (in)	32.7
RC (US) (in)	215.9
Rim Rec	DW 20 B
Rim Alt	DW 21 B; DW 23 B
ECE	E4-106R-000624
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
40	5160	6020	6780	7530	8280	8930	9890	10700
30	5420	6330	7120	7900	8700	9370	10390	11290
25	5610	6550	7360	8180	9010	9700	10760	11680
20	5940	6930	7790	8660	9520	10270	11390	12370
5 LT	6920	8070	9080	10090	11100	11960	13260	14410
5 HT	5940	6930	7790	8660	9520	10270	11390	12370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..