



US standard



GROWING TOGETHER

AS 509



PRODUCT DATA SHEET



Bias



166

Performance



Durability



High Load Capacity



Self-Cleaning



Traction



AS 509

AS 509 has been specially designed for trailers, balers and implement machinery. It ensures high load capacity at low inflation pressure protecting crops. AS 509 provides great traction and self-cleaning properties.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 22.5"	94064878	550/45 - 22.5	AG 16.00	-	21.3	41.9	18.9	128.0	37	154	STD	12	TL	141 A8/ 137 B	153 A8/ 149 B
	94051038	550/45 - 22.5	AG 16.00	-	21.3	41.9	18.9	128.0	37	174	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling