



AW 909

Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

US Standard

Construction

◇ Bias

Machinery

Agriculture ■ Baler



Version	STANDARD
Tire Type	TL
Tyre size	15.0/55-17
LI/SS	

Dimensions US Standard

USA Code	94010813
SW (in)	15.4
OD (in)	33.5
SLR (in)	14.8
RC (in)	98.0
Rim Rec	13.00
Rim Alt	13
ECE	E4-106R-001547

Load Capacity (US)

mph / psi	52
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..