



IS standard



GROWING TOGETHER

MAGLIFT RIM GUARD



PRODUCT DATA SHEET



Solid



MAGLIFT RIM GUARD

MAGLIFT (RIM GUARD) is specially engineered and designed for heavy duty forklifts used in industrial and logistic facilities. Its aggressive and robust tread pattern provide superior forward and lateral traction and excellent steering control. In addition, the wide center rib provides a low rolling resistance. The solid construction of MAGLIFT (RIM GUARD) features a high load capacity and an outstanding comfort, while its specially designed rim guard ensures protection against wheel damage. In addition, this tire shows excellent cut and chip resistance resulting in a longer tire life. MAGLIFT (RIM GUARD) reinforced structure eliminates slippage risk whilst the special bead shape simplifies mounting operations on the rim.

Technologies



Heavy Duty

Performance



Traction



Steering Control



Low Rolling Resistance



High Load Capacity



Cut and Chip Resistance



Durability

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
											Rec.	Alt.
Ø 10"	6.50 - 10	-	-	-	STD	154	575	-	-	21	5.00 F - 10	-
	6.50 - 10	-	-	-	STD	154	575	-	-	21	5.50 F - 10	-
Ø 12"	7.00 - 12	-	-	-	STD	168	658	-	-	23	5.00 S - 12	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference