



IS standard



GROWING TOGETHER

# AW 715



PRODUCT DATA SHEET



Radial



149



# AW 715

**UK** AW 715 is a high-performance radial tire for a wide range of agricultural implements designed for maximum operational efficiency and transport performance. The steel-belted construction enhances durability and stability, as well as resistance to punctures and stubble damage. The large contact patch combined with a rounded shoulder design protects grassland and reduces soil compaction, while the grooved tread design delivers superior traction on varied terrain. AW 715 features a robust carcass supporting heavy loads at speeds up to 65 km/h (40 mph), making it ideal for demanding agricultural operations and transport applications. This tire also stands out for smooth rolling, while the low aspect ratio further improves flotation.

**Technologies**



Steel Belted



Rounded Shoulder Technology

**Performance**



Durability



Stability



Stubble Resistance



High Puncture Resistance



Reduced Soil Compaction



High Load Capacity



Excellent flotation



Ideal for grassland

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 17"	500/50 R 17	149 D	16.00	-	503	940	433	2890	450	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.