



XL GRIP (L3)



Description

XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.

UM

US Standard

Construction

⊠ Bias

Machinery

Industrial & Construction ▪ Loader,OTR ▪ Loader

Version STANDARD

Tire Type TL

Tyre size 23.5-25

LI/SS

Dimensions US Standard

USA Code	94015870
OD (US) (in)	64.0
SLR (US) (in)	29.2
RC (US) (in)	189.4
Rim Rec	19.50/2.5
TRA Code	E3/L3

Load Capacity (US)

mph / psi	44	54
30	16100	-
5	-	24000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..