



IS standard



GROWING TOGETHER

AT 111



PRODUCT DATA SHEET



Bias



AT 111

AT 111 is suitable for all-terrain sport racing with ATVs. An "HD" version with a deep tread is available for users who need improved durability and traction.

Performance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 8"	AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	2	TL	-
	AT 18 X 10 - 8	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 20 X 11 - 8	9.0 AT	8.5 AT	282	508	-	-	STD	6	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
Ø 9"	AT 18 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	4	TL	-
	AT 20 X 11 - 9	9.0 AT	8.5 AT	279	508	-	-	STD	6	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
Ø 10"	AT 18 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	254	457	-	-	STD	4	TL	-
	AT 19 X 6 - 10	5.0	-	152	472	-	-	STD	4	TL	-
	AT 20 X 6 - 10	5.0	-	152	500	-	-	STD	2	TL	-
	AT 20 X 6 - 10	5.0	-	152	500	-	-	STD	4	TL	-
	AT 20 X 11 - 10	9.0 AT	8.5 AT	275	508	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

Performance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 10"	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	4	TL	-
	AT 21 X 7 - 10	5.5 AT	6.0 AT	178	541	-	-	STD	6	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	4	TL	-
	AT 22 X 7 - 10	5.5 AT	6.0 AT	175	559	-	-	STD	6	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	208	559	-	-	STD	6	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	4	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	282	559	-	-	STD	6	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	4	TL	-
	AT 23 X 7 - 10	5.5 AT	6.0 AT	178	584	-	-	STD	6	TL	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference