



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 51



PRODUCT DATA SHEET



Radial

L-5

A2

229

Technologies



Extra Deep Tread

Performance



Traction



Cut Resistance



Stability



Durability



EARTHMAX SR 51

RADIAL OTR TIRES

EARTHMAX SR 51 (L-5) is an All Steel radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
															Rec.	Alt.
Ø 25"	94046249	17.5 R 25	TL	*	176 A2	CRC	L-5	-	55.0	17.2	24.8	161.8	77	552	14.00/1.5	-
	94045822	20.5 R 25	TL	*	186 A2	CRC	L-5	-	60.8	21.2	27.7	183.1	86	822	17.00/2.0	-
	94046256	23.5 R 25	TL	*	195 A2	CRC	L-5	-	65.4	24.1	29.3	192.2	97	1120	19.50/2.5	-
	94069828	23.5 R 25	TL	**	201 A2	CRC	L-5	-	65.4	24.1	29.3	192.2	97	1140	19.50/2.5	-
Ø 29"	94051113	29.5 R 29	TL	*	211 A2	CRC	L-5	-	78.3	30.6	33.1	231.2	118	1917	25.00/3.5	24.00/3.5; 26.00/3.5
	94067145	875/65 R 29 (35/65 R 29)	TL	**	221 A2	CRC	L-5	-	73.7	34.6	32.0	221.1	116	2033	27.00/3.5	27.00/3.0; 28.00/3.5
Ø 33"	94066230	35/65 R 33	TL	**	224 A2	CRC	L-5	-	81.1	35.6	34.3	239.4	120	2276	28.00/3.5	-
	94069866	35/65 R 33	TL	***	229 A2	CRC	L-5	-	81.1	35.6	34.3	239.4	120	2394	28.00/3.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference