



## AGRIMAX FORCE

### Description

AGRIMAX FORCE the high-end product of BKT is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester



Version	STANDARD
Tire Type	TL
Tyre size	if800/70R42
LI/SS	186;D

## Dimensions US Standard

USA Code	94073641
SW (in)	31.3
OD (in)	84.6
SLR (in)	37.4
RC (in)	252.0
Rim Rec	DW 27 B
Rim Alt	DW 25 B; DW 28 B; DW 30 B
ECE	E4-106R-002650
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
<b>45</b>	8950	10280	11810	13340	14860	16380	17910	19060
<b>From 40 to 25</b>	9840	11310	12980	14660	16340	18010	19690	20900
<b>20</b>	10230	11760	13500	15240	16990	18730	20470	21780
<b>12</b>	10630	12210	14020	15830	17640	19440	21250	22620
<b>5</b>	12500	14360	16490	18620	20740	22870	25000	26600
<b>Upto 20 Cyc</b>	12790	14690	16880	19060	21230	23410	25580	27230
<b>Upto 10 Cyc</b>	15260	17530	20120	22720	25320	27910	30510	32460
<b>Upto 5 Cyc</b>	16730	19220	22070	24920	27770	30610	33460	35600
<b>5HT</b>	10230	11760	13500	15240	16990	18730	20470	21780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..