



EARTHMAX SR 55

Description

EARTHMAX SR 55 is an All Steel Radial tire specially designed for loaders and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability.



UM

US Standard

Construction

 Radial

Machinery

OTR ■ Dozer

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 29.5R29

LI/SS 223;A2

Dimensions US Standard

USA Code	94515271
OD (US) (in)	79.1
SLR (US) (in)	35.9
RC (US) (in)	238.1
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5; 26.00/3.5
TRA Code	L5S

Load Capacity (US)

mph / psi	73	76	80	83	87	91	94	98	102	105	109	112	116
5	43000	44100	45400	46700	49400	50700	52000	53600	55100	56800	58400	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..