



AGRIMAXFACTOR

Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	580/70R42
LI/SS	158;D

Dimensions IS Standard

SW (IS) (mm)	577
OD (IS) (mm)	1879
SLR (IS) (mm)	856
RC (IS) (mm)	5693
Rim Rec	W 18 L
Rim Alt	DW18L;DD18L
ECE	E11-106R-0010076
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
65	2340	2720	3105	3485	3870	4250
50	2460	2860	3260	3665	4065	4465
40	2545	2960	3380	3795	4210	4625
30	2690	3130	3570	4010	4450	4890
10 LT	3135	3645	4160	4670	5185	5695
10HT	2690	3130	3570	4010	4450	4890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..