



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor



Version

SPECIAL

Tire Type

TL

Tyre size

650/85R42

LI/SS

183;D

Dimensions US Standard

USA Code	94515875
SW (US) (in)	26.8
OD (US) (in)	85.0
SLR (US) (in)	36.9
RC (US) (in)	252.5
Rim Rec	DW 23 B
Rim Alt	DW20B;DW21B
ECE	E11-106R-0011307
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29
45	8770	10170	11570	13160	14560	15960	17550
from 40 to 25	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17900	19680
12	10030	11630	13240	15050	16640	18250	20060
5	10600	12300	14000	15910	17600	19300	21220
Upto 20 Cyc	10950	12690	14440	16410	18170	19920	21890
Upto 10 Cyc	13060	15160	17240	19600	21680	23780	26130
Upto 5Cyc	14320	16600	18890	21470	23760	26060	28640
5 HT	9830	11410	12980	14750	16320	17900	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..